

## Permanent Split Capacitor Condenser Fan 5.0" Diameter, Totally Enclosed Air Over (TEAO)



### APPLICATIONS:

Residential condensing unit fan motor.

### FEATURES:

- 42" Leads
- Shaft Down Mount
- #8-32 Studs  
Fig A: 4.312" dia. bolt circle  
Fig B: 4.464" dia. bolt circle
- Designed for use with 370V Capacitor
- 1/2" Dia. Shaft with Flat
- Reversible Rotation
- Automatic Reset Thermal Overload Protector
- **Discount Symbol: DS-3HAC**




Figure A




Figure B

### "Clam Shell" Single Speed, Stud Mount, Without Capacitor (Fig A)

HP	RPM	Voltage	Catalog Number	Bearings	Cap. MFD	Amps	Shaft N	Shell XI	Total C	Ship Wt.	Notes	OEM
1/10	1075	208-230	2243	Ball	5.0	0.75	2.7	4.1	6.8	10		
1/8	1075	208-230	2249	Ball	5.0	0.90	2.7	4.1	6.8	10		
1/5	1075	208-230	2246	Ball	5.0	1.60	2.7	4.9	7.6	10		
1/4	1075	208-230	2250	Ball	7.5	1.70	2.7	4.9	7.6	10		

### 5.0" Single Speed, Stud Mount, Without Capacitor (Fig B) 4.464 BC

HP	RPM	Voltage	Catalog Number	Bearings	Cap. MFD	Amps	Shaft N	Shell XI	Total C	Ship Wt.	Notes	OEM
1/20	1625	230	1989P	SAB	3.0	0.8	2.5	3.8	6.3	8	H35, H42, 98	CO
1/8	1550	230	1675	SAB	5.0	0.8	3.0	3.8	6.8	9	H35	TR
1/8-1/12	1075	208-230	5440H	Ball	5.0	0.8	3.0	5.0	8.0	8		
1/6	1075	208-230	1901	SAB	5.0	1.0	2.0	3.8	5.8	11.4		LE
1/4-1/6	1075	208-230	5441H	Ball	5.0	1.5	3.0	5.5	8.5	10		

TR= Trane    CO = Copeland    LE = Lennox

Note 98: 50/60 Hz

Note H35: Open Air Over

Note H42: Shaft-down mounting